

REVERSE FORWARD

ROTARY TILLER

Salient Feature:

- Best Suitable for tillage and earthing up operation.
- Specially designed J-Type boron steel blades.
- Heavy duty robust structure
- Twin direction single speed gear box
- Best suitable for controlling weeds.
- Improves infiltration & seepage of water.
- Special design for sugarcane inter cultivation and earthing up operation for better growth.

World's only rotary tiller with robust dual tubular & angular support for eliminating mechanical vibrations to almost zero.



SUGARCANE
SPECIAL



SAVE LABOUR TIME & OPERATIONAL COST



REVERSE FORWARD ROTARY TILLER



WALK AROUND REVERSE FORWARD

TECHNICAL SPECIFICATION

Type	SLRT 0.65	SLRT 0.85
Tillage width (in/cm)	22/56	28/72
Total Width (in/cm)	31/79	37/95
Total Length (in/cm)	40/101	40/101
Overall Height (in/cm)	39/100	39/100
No. of Blade	18	22
PTO Speed (RPM)	540	540
Types of Blades	J-TYPE	J-TYPE
Weight (KG) Approx.	155	170
Tractor Power (HP)	15-30	15-30
3-Point Hitch Type	Cat-I	Cat-I
Transmission type	CHAIN	CHAIN
Rotor tube diameter (in/cm)	3/7.3	3/7.3
Rotor Swing Dia(in /cm)	21/53	21/53
Driveline Safety	SHEAR BOLT	SHEAR BOLT
Recommended Row to Row distance (feet)	3.5 to 4 feet	4.5 to 5 feet



SPECIALY DESIGN
FOR 15-30 HP
TRACTOR



AVAILABLE WITH
J TYPE BORON STEEL
BLADES



HELICAL
ARRANGEMENTS OF
BLADES



BEST FOR EARTHING UP
OPERATION FOR
SUGARCANE FIELD



SPECIALY DESIGNED
GEARBOX FOR
OPERATION ROTOR

SAVE LABOUR TIME & OPERATIONAL COST

SONALIKA INDUSTRIES

(A UNIT OF INTERNATIONAL CARS & MOTORS LTD.)

Works & Admin Office: Vill. Chak Gujran, Jalandhar Road, Hoshiarpur- 146 022 (Pb.), India

Phone: +91 99149-34522, +91 1882-501320 | Email: info@sonalikaindustries.com | Website: www.sonalika.com/agrosolutions

Auth. Dealer