

CHALLENGER ALPHA

ROTARY TILLER

Salient Feature:

- Challetillage rotary tiller is a secondary tillage implement offering best in class pulverization and optimum seed germination
- Robust hitch pyramid for better load distribution.
- Equipped with heavy duty multispeed gearbox for wider range of rotor speed.
- Ensures excellent cutting and mixing of crop residue
- Renowned 13x23 Crown pinion for heavy duty work.

World's only rotary tiller with robust dual tubular & angular support for eliminating mechanical vibrations to almost zero.

BOSS
OF TILLAGE



AVAILABLE IN SINGLE & MULTISPEED //

FOR ANY QUERY GIVE A MISSED CALL
8955011122

CHALLENGER ALPHA


ROTARY TILLER



WALK AROUND CHALLENGER ALPHA

TECHNICAL SPECIFICATION

Size	5 Feet	5.5 Feet	6 Feet	7 Feet	8 Feet	9 Feet	10 Feet
Tillage width (in/cm)	59/149	66/168	69/175	79/200	87/220	106/269	114/291
Total Width (in/cm)	70/179	77/194	80/204	90/230	98/249	118/298	126/320
Total Length (in/cm)	35/90	35/90	35/90	35/90	35/90	35/90	35/90
Height (in/cm)	44/112	44/112	44/112	44/112	44/112	44/112	44/112
Weight (KG) Approx	430	445	460	490	536	570	640
PTO Speed RPM	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000	540/1000
No. Of Blades	36	36/39	42	48	54	60	66
Types of Blades	L/C	L/C	L/C	L/C	L/C	L/C	L/C
Suitable Tractor HP	45-50	50-55	50-55	55-60	60-65	70-75	75-90
3-Point Hitch Type	Cat-II	Cat-II	Cat-II	Cat-II	Cat-II	Cat-II	Cat-II
Transmission type	GEAR	GEAR	GEAR	GEAR	GEAR	GEAR	GEAR
Rotor tube diameter (in/cm)	3.5/9	3.5/9	3.5/9	3.5/9	3.5/9	3.5/9	3.5/9
Rotor Swing dia (in/cm)	18/46	18/46	18/46	18/46	18/46	18/46	18/46
Driveline safety Device	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT



#4 no. of damper spring for 7 feet & above variants.

*The Product & Specifications are subject to change/discontinue without any notice on the sole discretion of manufacturer.



DU CONE MECHANICAL OIL SEALS IDEAL FOR DRY & WET LAND OPERATIONS



AVAILABLE WITH L&J TYPE BORON STEEL BLADES



HELICAL ARRANGEMENTS OF BLADES



ROBUST STRUCTURE FOR HEAVY VIBRATION FREE FILED OPERATION




OIL IMMERSED SIDE BEARING

ALPHA		SIDE GEAR	
A	B	r.p.m.	r.p.m.
13	22	—	238
15	20	163	—
16	19	183	—
17	18	206	—
18	17	231	—
19	16	259	—
20	15	291	—

Pinion 13
Crown 23

Boron Steel Blades



- 20% longer life.
- Hard to break & bend.
- Saves money & time.

AVAILABLE IN SINGLE & MULTISPEED

SONALIKA INDUSTRIES

(A UNIT OF INTERNATIONAL CARS & MOTORS LTD.)

Works & Admin Office: Vill. Chak Gujran, Jalandhar Road, Hoshiarpur- 146 022 (Pb.), India

Phone: +91 99149-34522, +91 1882-501320 | Email: info@sonalikaindustries.com | Website: www.sonalika.com/agrosolutions

Auth. Dealer