CULTIVATOR

HEAVY DUTY SPRING LOADED TILLER

Salient Feature:

- Secondary tillage implement for aerating & loosing of soil.
- Better pulverization for smooth seed bed preparation.
- Best suitable for use in stoney & rooty soil conditions.
- Spring provides the damping effect like if one tine is obstructed, the other continues to work at proper depth.

Heavy duty springs with 10 mm WD for over coming obstruction like stones / hooks etc.

Secondary tillage implement for better soil pulverization, efficient uprooting of weeds and left over crop residue.

SONALIKA

HEAVY DUTY SPRING TO ABSORB SUDDER

FOR ANY QUERY GIVE A MISSED CALL 8955011122

CULTIVATOR

HEAVY DUTY SPRING LOADER TILLER



WALK AROUND CULTIVATOR

TECHNICAL SPECIFICATION

DESCRIPTION		9 TINE	9 TINE	11 TINE	13 TINE
FRAME (mm)		75x40 (Channel)	100x50 (Channel)		
TINES (mm)	Π	50x25 FORGED			
LENGTH (mm)		2039		2492	2945
WIDTH (mm)	l₩	878			
HEIGHT (mm)	Ī	1157			
3 POINT LINKAGE		F-65X16 & R - 50X16			
SPRING		10 WD / 50 OD / 28.5 Coil			
WEIGHT (kg.) approx.	ΔI^{Δ}	270 Kg.	290 Kg.	370 Kg.	440 Kg.
TRACTOR POWER (hp)		45+		55+	65+



HEAVY DUTY FRAME CHANNEL FOR TOUGHEST OPERATION



BEST QAULITY HEAVY DUTY SPRIGS



FORGED TINES FOR HARD SOIL MADE UP OF ENP MATERIAL



SUPERIOR POWDER COATED PAINT PREVENT FROM RUST



SAVE LABOUR TIME & OPERATIONAL COST

SONALIKA INDUSTRIES

(A UNIT OF INTERNATIONAL CARS & MOTORS LTD.)

Works & Admin Office: Vill. Chak Gujran, Jalandhar Road, Hoshiarpur- 146 022 (Pb.), India

Phone: +91 99149-34522, +91 1882-501320 | Email: info@sonalikaindsutries.com | Website: www.sonalika.com/agrosolutions

